

Boomlift / Manlift

Used Boom Lift Temecula - In terms of popular aerial machinery, the boom lift is one of the most recognizable. Also referred to as elevating work platforms, aerial devices, cherry pickers, mobile elevating work platforms and aerial work platforms, boom lifts are capable of completing jobs at higher elevations easily and efficiently. There are many places to find boom lifts at work including warehouses, contractors, various companies and in retail stores. Workers need to remain safe as they access locations at higher altitudes. There is a wide variety of boom lift models to choose from. Many models are capable of being operated by a single individual. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. Since ladders require even, solid ground for setting them up safely, they can be unreliable in the agricultural industry. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Boom lifts make working over top of obstacle much easier as many models have been engineered to travel up and over items. Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. With a variety of joints allowing the machine to bend over or under items, the articulated boom lift is helpful for numerous applications. The articulated boom sections can move independently to grant operators access to many locations. Articulated booms feature a tight turning radius, making them ideal for hallways and narrow storage corridors. The dual-fuel boom lifts provide service in both exterior and interior locations. Diesel models are used outside while electric boom lifts are implemented in interior locations. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. Articulated boom lifts are utilized commonly for working on overhead power lines and wires. Certain models are outfitted with water cannons to be used in firefighting applications. Some models are built for extended reach applications and outfitted with telescoping sections. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. No second operator is required as the platform operator can extend the lift with the controls. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Boom lifts that have an extension between the platform and the end of the primary boom are called the jib. Certain models offer an additional articulation point or hinge that allows the platform to travel horizontally and vertically. Jibs are an option on many telescoping and articulating boom lifts. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. In 1985, the first Genie Z-30/20 articulating Z-boom was introduced; their up-and-over capacity make them instantly popular and this design continues today. Proper Safety Measures Of course, safety is the

highest priority when operating any type of boom lift. It is essential that all potential safety hazards are known to anyone working within the area to maintain a safe atmosphere. Safe operation of the machine and personal safety must be paramount. Before operating the machine, effective communication and essential safety gear need to be in place. Be aware of any battery gases, engine fuels, combustible items, lit cigarettes or open flames near the machine and do not operate if any flammable or combustible items are present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. It is important to maintain a clean work space around charging stations and work surfaces since clutter or tools could puncture tires or damage the machine or its components. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. Stabilizing the weight is accomplished supportive devices to lift and distribute the load. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single use components and fasteners cannot be reused due to their risk of failure. Environmental contamination can be prevented by properly discarding oils safely in an approved container. Safety can be increased with proper lighting and adequate ventilation along workbenches and within workshops and garages. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report Main aspects of the boom lift are categorized and divided to facilitate the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. A list of single maintenance procedures that need to be conducted at 50-hour and 150-hour intervals is known as commissioning. Annual and Quarterly maintenance procedures need to be performed once or multiple times a year. There are a variety of programmed maintenance procedures based on preparing the machine for pre-delivery machine operating. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.